

(単位mm)

形名 WCI-	内側寸法の直径	形名 WCI-	内側寸法の直径
3.43	623.0	80.0	26.700
3.56	599.0	83.1	25.700
3.71	576.0	86.1	24.800
4.01	532.0	93.2	22.900
4.17	512.0	97.0	22.000
4.34	492.0	101	21.100
4.69	455.0	109	19.500
4.88	437.0	114	18.800
5.08	420.0	118	18.150
5.50	388.0	127	16.850
5.72	373.0	129	16.250
5.95	359.0	136	15.650
6.43	332.0	148	14.450
6.69	319.0	154	13.850
6.95	307.0	161	13.250
7.54	283.00	174	12.300
7.85	272.00	179	11.900
7.99	262.00	186	11.500
8.82	242.00	198	10.760
9.16	233.00	207	10.300
9.53	224.00	219	9.700
10.3	207.00	232	9.220
10.7	199.00	239	8.920
11.2	191.00	248	8.620
12.1	176.50	266	8.020
12.6	170.00	277	7.720
13.1	163.50	288	7.420
14.1	151.00	308	6.940
14.7	145.00	317	6.740
15.3	139.50	327	6.520
16.5	129.00	348	6.140
17.2	124.00	359	5.940
17.9	119.00	372	5.740
19.4	110.00	398	5.360
20.1	106.00	414	5.160
20.9	102.00	429	4.950
22.7	94.00	457	4.670
23.6	90.40	467	4.570
24.5	87.00	478	4.470
26.6	80.40	512	4.170
27.7	77.20	539	3.960
28.7	74.40	568	3.760
31.1	68.60	613	3.480
32.3	66.00	632	3.380
33.7	63.40	651	3.280
36.4	58.60	696	3.070
37.8	56.40	721	2.960
39.4	54.20	746	2.860
42.7	50.00	799	2.670
44.4	48.10	831	2.570
46.2	46.20	876	2.440
49.9	42.80		
51.8	41.20		
53.9	39.60		
58.3	36.60		
60.6	35.20		
63.2	33.80		
68.2	34.30		
70.9	30.10		
73.9	28.90		

内側寸法の許容差

(標準級)

形名	許容差
WCI-3.3~WCI-28.7	± (公称内側寸法の直径) × 1/500
WCI-30~WCI-165	± (公称内側寸法の直径) × 3/2000
WCI-174~WCI-890	—

(精密級)

形名	許容差
WCI-3.3~WCI-165	± (公称内側寸法の直径) × 1/1000
WCI-174~WCI-220	± 0.010
WCI-232~WCI-890	± 0.008